



# Test Report : SFTN01N-12N

---

1W SMD Package DC-DC Unregulated Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

## ■ SAFETY TEST

Safety Test

## ■ RELIABILITY TEST

Environment Test

Other Test

## DESIGN VERIFY TEST

### OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	VOLTAGE ACCURACY	-5.0% ~ +5.0 % (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	-0.10%	P
2	RIPPLE & NOISE	100 mVp-p (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	70 mV	P
3	LINE REGULATION	-12% ~ +12% (Max)	I/P:21.6VDC~26.4VDC O/P:FULL LOAD Ta:25°C	-10.89% ~ +10.87%	P
4	LOAD REGULATION	-8% ~ +8% (Max)	I/P:24VDC O/P:10% LOAD~FULL LOAD Ta:25°C	-1.16% ~ +1.71%	P

### INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	EFFICIENCY	80% (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	82.33%	P
2	DC CURRENT	55 mA / FULL LOAD (Max) 10 mA / NO LOAD (Max)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	50.72 mA / FULL LOAD 6.51 mA / NO LOAD	P

### PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	SHORT PROTECTION	0.5 second max.	I/P:26.4VDC O/P:FULL LOAD Ta:25°C	OK	P

## SAFETY TEST

### SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	WITHSTAND VOLTAGE	I/P-O/P:3K VDC/min	I/P-O/P:3K VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>10GΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>10GΩ NO DAMAGE	P

**RELIABILITY TEST**
**ENVIRONMENT TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC												
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=85°C 3. HIGH AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:60% LOAD Ta=95°C			P;												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>CENTER</td> <td>35.1°C</td> <td>92.5°C</td> <td>101.3°C</td> </tr> </tbody> </table>				NO	Position	P/N	1	2	3	1	CASE	CENTER	35.1°C	92.5°C	101.3°C
NO	Position	P/N	1	2	3												
1	CASE	CENTER	35.1°C	92.5°C	101.3°C												
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:24VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P												

**OTHER**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.95693 M.T.B.F : 1045 KHRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG